TEST REPORT

NAME: CERAMIC TILES

WORK SIZE: 250X398.5X7.2-7.4MM Test Report No.:(2020)MJJC-1273

Test Standard: GB/T 4100-2015 Dry Pressed Tiles Appendix L. BIII (E>10%)

	ical Data				
Serial No.	Test Items		Provisions of Standard	Test Result	Judgement
	Side Length		±0.5% Max ±2.0mm	-0.1 %~+0.1% Max:+0.4mm	Passed
1	Side Width		±0.5% Max ±2.0mm	-0.2%~-0.1% Max: -0.6mm	Passed
	Thickness		±10% Max ±0.5mm	-1%~+2% Max: 0.1mm	Passed
2	Straightness of sides		±0.30% Max±1.5mm	-0.1~+0.2% -0.2~+0.2mm	Passed
3	Deviation from rectangularity		±0.50% Max±2.0mm	-0.1~+0.2% -0.2~+0.3mm	Passed
4	Surface flatness	Centre curvature	-0.30~+0.50% Max-1.5~+2.0mm	+0.0%~+0.3%	Passed
		Edge curvature	-0.30~+0.50% Max-1.5~+2.0mm	-0.1%~+0.3%	Passed
		Warpage	±0.50% Max±2.0mm	-0.1%~+0.3%	Passed
5	Surface quality		A minimum of 95% of the tiles shall be free from visible defects that would impair the appearance of a major area of tiles	CONFIRMED	Passed
6	Water Absorption		Average: E > 10% Single Min value > 9%	Average: 17% Single Min value: 17%	Passed
7	Breaking strength, N		Thickness <7.5mm ≥ 200N	433N	Passed
8	Modulus of rupture, Mpa		Thickness<7.5mm, ≥15Mpa	17Мра	Passed
9	Crazing Resistance		Fully resistance	CONFIRMED	Passed
10	Thermal shock resistance		Fully resistant	CONFIRMED	Passed
11	Impact resistance		Test method available	Avaerage:0.58	

12	Resistance to Surface abrasion of glazed tiles	Report abrasion class and cysles passed	Class 3 at 750 revolutions	
13	Moisture Expansion	Test method available	Avaerage:0.01%	
14	Resistance to low concentrations of acids and alkalis	Manufacturer to state Classification	GLA	
15	Resistance to Chemicals(Resistance to household chemicals and swimming pool	Min: Class GB	GA	Passed
16		Min: Class 3	Class 5	Passed

